



Pneus OTR - E3/L3



Detalhes do produto

Tamanho	PR	Nome do Padrao	Diametro Total (mm)	Largura da Secao (mm)	Aro	Carga (kgs)	Pressao (Kpa)	Tipo	Prof. Sulcos
12h00-16h00	14	E-3/L-3	884	244	8,5	1705	680	TL/TTF	20mm
14h00-24h00	20	E-3/L-3	1370	375	11	4625	475	TL/TTF	30mm
14h00-24h00	24	E-3/L-3	1370	375	11	5150	575	TL/TTF	30mm
14h00-24h00	28	E-3/L-3	1370	375	11	5600	650	TL/TTF	33mm
16/70-20	16	E-3/L-3	1067	635	13	2600	350	TL/TTF	22mm
16/70-24	16	E-3/L-3	1067	635	13	2600	350	TL/TTF	26mm
20,5/70-16	14	E-3/L-3	910	350	10.00	1600	390	TTF	26mm
15,5-25	12	E-3/L-3	1275	395	12,00/1,3	3250	250	TL/TTF	28mm
15,5-25	16	E-3/L-3	1275	395	12,00/1,3	3850	325	TL/TTF	30mm
17,5-25	16	E-3/L-3	1350	445	14,00/1,5	4250	300	TL/TTF	30mm
17,5-25	20	E-3/L-3	1350	445	14,00/1,5	5000	400	TL/TTF	31mm
20,5-25	16	E-3/L-3	1490	520	17,00/2,0	5450	275	TL/TTF	31mm
20,5-25	20	E-3/L-3	1490	520	17,00/2,0	6000	325	TL/TTF	31mm
20,5-25	24	E-3/L-3	1490	520	17,00/2,0	6700	400	TL/TTF	33mm
23,5-25	20	E-3/L-3	1615	595	19,50/2,5	7300	300	TL/TTF	33mm
23,5-25	24	E-3/L-3	1615	595	19,50/2,5	8000	350	TL/TTF	33mm
23,5-25	28	E-3/L-3	1615	595	19,50/2,5	8750	400	TL/TTF	34mm
26,5-25	28	E-3/L-3	1743	645	22,00/3,0	10000	350	TL/TTF	35mm