

Catálogo de Produtos
Pneus OTR





TB596



TB516



TL538S+

Medida	Modelo	Classificação Por estrela	App.	Largura do Aro	Espaçamento Min. Duplo		Dimensões Aproximada Inflado				Dimensões Carregado		Profundidade do Sulco		Capacidade de desempenho (TKPH)			Tipo	
							Largura Total		Diâmetro Total		Carga Estática								
					Pol.	mm	Pol.	mm	Pol.	mm	Pol.	mm	32nds	mm	T1	T2	T3	TT	TL
14.00R24	TB516	*	L-2	10.00VA			14.8	375	53.9	1368			31.5	25.0				TL	
17.5R25	TB516	*	L-3	14.00/1.5			17.5	445	53.1	1348	23.6	600	32.8	26.0				TL	
	TB516	**	L-3	14.00/1.5			17.5	445	53.1	1348	23.6	600	32.8	26.0				TL	
	TB596	*	L-2	14.00/1.5			17.5	445	53.1	1348			35.3	28.0				TL	
	TB596	**	L-2	14.00/1.5			17.5	445	53.1	1348			35.3	28.0				TL	
20.5R25	TL538S+	*	L-5	17.00/2.0			20.5	521	61.0	1548	25.8	656	88.2	70.0				TL	
	TL538S+	**	L-5	17.00/2.0			20.5	521	61.0	1548	25.8	656	88.2	70.0				TL	
	TB516	*	L-3	17.00/2.0			20.5	521	58.8	1493	25.8	656	37.8	30.0				TL	
	TB516	**	L-3	17.00/2.0			20.5	521	58.8	1493	25.8	656	37.8	30.0				TL	
	TB596	*	L-2	17.00/2.0			20.5	521	58.8	1493			39.1	31.0				TL	
	TB596	**	L-2	17.00/2.0			20.5	521	58.8	1493			39.1	31.0				TL	

10 KM/H (5 MPH)															
14.00R24	550														KPa
	80														PSI
	6900*														KG
	15200*														LBS
17.5R25	400	425	450	475	500	525	550	575	600	625	650				KPa
	58	62	65	69	73	76	80	83	87	91	94				PSI
	6000	6150	6500	6700	7100*	7300	7500	7750	8000	8250	8500**				KG
	13200	13600	14300	14800	15700*	16100	16500	17100	17600	18200	18700**				LBS
20.5R25	400	425	450	475	500	525	550	575	600	625	650				KPa
	58	62	65	69	73	76	80	83	87	91	94				PSI
	8000	8250	8750	9000	9500*	9750	10000	10300	10900	11200	11500**				KG
	17600	18200	19300	19800	20900*	21500	22000	22700	24000	24700	25400**				LBS

OTR



TB536



TB515



TB596

Medida	Modelo	Classificação Por estrela	App.	Largura do Aro	Espaçamento Min. Duplo		Dimenções Aproximada Inflado				Dimensões Carregado		Profundidade do Sulco		Capacidade de desempenho (TKPH)			Tipo	
							Largura Total		Diâmetro Total		Carga Estática								
					Pol.	mm	Pol.	mm	Pol.	mm	Pol.	mm	32nds	mm	T1	T2	T3	TT	TL
14.00R24	TB536	*	G-2	10.00VA	17.7	450	14.8	375	53.9	1368			31.5	25.0	110	140	170	TL	
	TB536	***	E-2	10.00W	17.7	450	14.8	375	53.9	1368			31.5	25.0				TL	
	TB515	*	G-2	10.00VA	17.7	450	14.8	375	53.9	1368			31.5	25.0				TL	
	TB596	*	G-2	10.00VA	17.7	450	14.8	375	53.9	1368			31.5	25.0				TL	
17.5R25	TB515	*	G-2	14.00/1.5			17.5	445	53.1	1348	24.0	610	34.0	27.0				TL	
	TB596	*	G-2	14.00/1.5			17.5	445	53.1	1348			35.3	28.0				TL	
20.5R25	TB515	*	G-2	17.00/2.0			20.5	521	58.8	1493	26.3	669	37.8	30.0				TL	
	TB596	*	G-2	17.00/2.0			20.5	521	58.8	1493			39.1	31.0				TL	

40 KM/H (25 MPH)									50 KM/H (30 MPH)							
14.00R24	200	225	250	275	300	325	350	375	450	475	500	525	550	575	600	KPa
	29	33	36	40	44	47	51	54	65	69	73	76	80	83	87	PSI
	2240	2430	2650	2800	3000	3250	3350	3650*	4000	4125*	4375	4500	4625	4750	5000	KG
	4940	5360	5840	6150	6600	7150	7400	8050*	8800	9100*	9650	9900	10200	10500	11000	LBS
	475	500	525						625	650	675	700	700			KPa
	69	73	76						91	94	98	102	102			PSI
17.5R25	9750	10000	10300						5150	5300	5450	5600**	5800***			KG
	21500	22000	22700						11400	11700	12000	12300**	12760***			LBS
	125	150	175	200	225	250	275	300								KPa
	18	22	25	29	33	36	40	44								PSI
	1850	2120	2360	2650	2900	3075	3350	3650*								KG
	4080	4680	5200	5840	6400	6800	7400	8050*								LBS
20.5R25	125	150	175	200	225	250	275	300								KPa
	18	22	25	29	33	36	40	44								PSI
	2430	2800	3150	3450	3875	4125	4375	4625*								KG
	5360	6150	6950	7600	8550	9100	9650	10200*								LBS

Endereço

**No. 56 Qingdao Middle Road
264200 Weihai, Shandong
P.R. China**

Telefone

America
+86-631-5330561
+86-631-5333990

Asia – Pacific
+86-631-5336370

Africa – Middle East
+86-631-5318926
+86-631-5322782

Europa
+86-631-5318745
+86-631-5322987

After-Sales Service
+86-631-5317138

Email

Triangle Global
globalsales@triangle.com.cn

Triangle Office in Europe
john.ruddy@triangle-eu.com

Triangle Office in Russia
info@triangle-shina.ru

Triangle Office in India
kcsp@triangleindia.co.in